




UNI EN ISO 9001:2015  
UNI EN ISO 14001:2015  
UNI EN ISO 45001:2018

<b>Name: ASPHALT SHOE</b> Description	<b>Code: MB2430Z9</b>	<b>MB24 FOOTWEAR - SPECIAL PROTECTION</b>
---------------------------------------	-----------------------	---

Ankle high shoe, specifically designed for asphaltists, made with an Action leather upper, PS-type composite midsole and aluminium toecap. The two-component sole made of polyurethane and nitrile rubber is flexible and at the same time extremely resistant. The nitrile rubber tread resistant to contact heat is free of dowels and scuffing, as it is specially designed to avoid leaving marks on the tar when working or laying the tar. The footbed is made of polyurethane foam with a felt bottom that provides excellent thermal insulation. Antistatic. The DRY PLUS lining in tightly woven polyester with extra protection in the heel area has a high draining power and considerably reduces the overheating effect from prolonged use.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category <b>II</b>	Colours <b>BLACK</b>	Available Sizes In stock: 39 - 47
Quantity/Carton  <b>5</b>	EC Standards EN ISO 20345  Safety Class: S2 PS HI HRO FO SC SR	Important Information Store clean footwear in a cool, dry place, away from heat sources and away from light. Before each use, check that the shoes are in perfect condition and replace them if they are not intact. The shoes must be cleaned with a soft brush and water. Do not use chemicals that could damage the materials. Storage and cleaning
Dexterity		